

FEATURES

APPLICATION	UCAN		ITW RED HEAD			HILTI				DEWALT			
	FR5 MAX	FR6 - SD	A7+	C6+	G5+	HY-270	HY-200 (A/R)	RE100	RE-500-V3	AC200+	AC100+ Gold	PE1000+	PURE 110+
Uncracked concrete	●	●	●	●	●		●	●	●	●	●	●	●
Cracked concrete	●	●	●	●	●		●	●	●	●	●	●	●
Hollow block	●		●	●		●					●		+
Saturated (per listing)	●	●	●	●	●		●	●	●	●	●	●	●
Water Filled (per listing)	●	●	●	●	●			●	●	●	+	●	●
Submerged (per listing)	●	●	●	●	●			●	●				●
Oversized holes	+	+	+	●	+								
Overhead	*	*	*	*			*	*	*	*	*	+	+
Cure time @ 20-25C	50 min	7 hr	45 min	6.5 hr	8 hr	30 min	A -30 min R -60 min	12 hr	6.5 hr	3 hr	45 min	10 hr	8 hr
Gel Time @ 20-25C	5 min	11 min	5 min	16 min	16 min	<4 min	A -4 min R -15 min	30 min	25 min	30 min	6 min	30 min	25 min
Compatible with Std Chalking gun?	Yes (10oz)	No	Yes (9.5)			No				Yes	Yes		

* Compliance with CSA A23.3 -14 is required.

+ May be suitable for specific applications.

APPROVALS & COMPLIANCY

APPLICATION	UCAN		ITW RED HEAD			HILTI				DEWALT			
	FR5 MAX	FR6 - SD	A7+	C6+	G5+	HY-270	HY-200 (A/R)	RE100	RE-500-V3	AC200+	AC100+ Gold	PE1000+	PURE 110+
Approvals/Listings	IAPMO MTO MTQ	ICC-ES MTO MTQ NSF 61	ICC-ES MTO NSF 61	CC-ES MTO NSF 61	CC-ES MTO NSF 61	ICC-ES	ICC-ES MTO NSF 61	ICC-ES MTO NSF 61	ICC-ES MTO NSF 61	ICC-ES MTO NSF 61	ICC-ES MTO NSF 61	ICC-ES NSF 61	ICC-ES MTO
ACI 318 compliant	●	●	●	●	●	●	●	●	●	●	●	●	●
CSA A23.3-14 Compliant	●	●					●	●	●				
Anchor Category	1	1	1				1	1	1	1	1		1
Seismic Zones	A - F	A - F	A - F	A - F	A - F		A - F	A - F	A - F	A - F	A - F	A - F	A - F
Design Software	●	●	●	●	●	●	●	●	●	●	●	●	●

BUILDING LASTING CONNECTIONS

UCAN

FASTENING PRODUCTS

- One of the broadest temperature ranges in the industry
- Standard caulking gun compatible (10oz)
- Low odour, styrene & MMA free
- Rapid gel and cure time
- Quick change nozzle for easy re-use
- Moisture insensitive, non-sag formula
- Contact UCAN's engineering / technical department for additional specifications or assistance
- The tabulated data on competitive products are based on published information at the time of the release of this document and is not construed as verified

